BlackPearl



Software-Defined Platform for Tiered Object and File Storage

Spectra Logic is at the forefront of data preservation, protection, and optimization.

<u>BlackPearl®</u> extends this legacy by delivering a robust, software-defined storage platform that seamlessly integrates with flash, disk, tape, and cloud—enabling organizations to secure and preserve their critical data at scale.



BlackPearl Nearline Object Gateway

- Integrates with Amazon S3compatible applications
- Optimized for large, unstructured datasets
- Policy-based data movement
- Seamless replication and data redundancy

BlackPearl Nearline Media Gateway

- Optimized for tape storage
- Advanced policy control
- Robust data protection for enhanced resilience
- Designed for tailored workflows

BlackPearl NAS



- Scalable to 20PB of raw storage in a single rack
- Data preservation and immutability
- Cost-effective storage (NFS, CIFS/SMB)

Object-Based Tape



- Compatible with Amazon S3-Glacier
- Fast retrieval of infrequently accessed data
- Deep archive tier for long-term data retention
- Scales to exabytes of storage

BlackPearl: Flexible, Resilient, and Future-Ready

The BlackPearl family provides scalable, policy-driven storage solutions with all-flash and hybrid disk/flash configurations. Designed for high availability, reliability, and cost-effective scalability, BlackPearl ensures seamless data access and control whether on-premises, in the cloud, or across a multicloud hybrid environment.

BlackPearl provides a future-ready storage foundation, optimizing data security, accessibility, and management for active archives, deep storage, and hybrid cloud workflows.



BlackPearl Technical Specifications

| | H3300 HDD+SSD-based Deployment Appliance | F7300 Flash-based Deployment Appliance | E2078 Disk Expansion Chassis |
|-------------------|--|--|---|
| Processor | AMD Milan CPU | AMD Genoa CPU | N/A |
| RAM | 256, 512G B | 512GB | N/A |
| Availability | Single node or Active/Standby | Single node or Active/Standby | N/A |
| Expansion | Up to 4x E2078 | Up to 8x E2078 | N/A |
| Protection | ZFS RAID dual-parity or triple-parity | | |
| Dimensions | 4U, 7x19x27(in), 17.8x48.3x68.6(cm) | 2U, 3.5x19x30(in), 8.9x48.3x76.2(cm) | 4U, 7x19x32(in), 17.8x48.3x81.3(cm) |
| Power Supplies | Dual, Redundant 1300W | Dual, Redundant 1600W | Dual, Redundant 1600W |
| Network | 1x 1 GbE mgmt; 1x 1 GbE IPMI 2x 10/25 or 40/100 GbE | 1x 10 GbE mgmt; 1x 1 GbE IPMI 2x 40/100 GbE | N/A |
| Connectivity | 6x PCIe (Gen4) slots 5x 4-prt 12Gb SAS HBAs 5x 4-prt 24Gb SAS HBAs 5x 4-prt 16Gb FC HBAs 5x 4-prt 32Gb FC HBAs | 2x PCle (Gen5) slots 2x 4-prt 12Gb SAS HBAs 2x 4-prt 24Gb SAS HBAs 2x 4-prt 16Gb FC HBAs 2x 4-prt 32Gb FC HBAs | SAS Interface |
| Capacity | 24x 3.5" HDD 4x 2.5" SSD | 24x 2.5" SSD | 78x 3.5" HDD |
| HDD's | 8, 20, 22TB SAS 8, 20TB SAS (SED) | N/A | 4, 8, 20, 22TB SAS 8, 20TB SAS (SED) |
| SSD's | 1.6, 6.4, 12.8, 25.6TB NVMe SSD (U.2) | 1.6, 6.4, 12.8, 25.6TB NVMe SSD (U.2) | N/A |
| Amb Temp | 32°F to 95°F (0°C to 35°C) (Altitude -200 ft to 10,000 ft) | | |
| Humidity | 5% to 95% relative humidity non-condensing, operating | | |
| Thermal | 4435 BTU/hr | 5460 BTU/hr | 5460 BTU/hr |
| Certifications | ENERGY STAR 2.0 for Servers | | |

a) Includes the front bezel.b) Weights are approximate.c) Includes optional cable management arm.

About Spectra Logic Corporation

Spectra Logic modernizes IT infrastructures to preserve, protect and defend data, from days to decades, whether on -premises, in a single cloud, across multiple clouds or in all locations at once. Our cost-effective solutions help organizations efficiently manage, migrate and store long-term data, from terabytes to exabytes, with features that make it ransom ware resilient



© Spectra Logic. All trademarks and registered trademarks are properties of their respective owners. Toll Free: 800-833-1132 • 303-449-6400 • 6285 Lookout Road • Boulder, CO 80301 USA